

### mosstype@mosstype.com

**Tel:** (201) 444-8000

150 Franklin Turnpike

Waldwick, N.J. 07463

**Fax:** (201) 444-0095

Copying and/or downloading of this information for the purpose of properly utilizing Mosstype Corporation product is allowed provided that (1) the information is copied in full with no changes unless prior agreement is obtained from Mosstype Corporation product, & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

Safety Data Sheet

Page 1 of 11

Proofing Ink Black (7640 0404 25)

Section I

Identification

**Manufacturer** 

Mosstype Corporation 150 Franklin Turnpike Waldwick, NJ 07463 201-444-8000

Emergency Telephone Number 1-800-255-3924 (Chem-Tel) Technical & SDS Information 201-444-8000

**Preparation Date** 01/01/2022

Recommended use: Proofing Print Plates

**Product Name:** Proofing Ink - Black Product Identification

7640 0404 25

Section 2 **Hazards Identification** 

**OSHA/HCS** status: This material is considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Classification of the:

substance or mixture ACUTE TOXICITY (oral) - Category 4

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) Category 2

**GHS Label elements Hazard pictograms** 







**Signal Word** Hazard statements:

Danger

Harmful if swallowed. Causes skin irritation.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated exposure.

Page 2 of 11

### **Precautionary statements**

Prevention: Wear protective gloves, protective clothing and eye or face protection. Keep away

from flames and hot surfaces. No smoking. Do not breathe vapor. Do not eat, drink

or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response: IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse

> mouth. Take off contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER or physician.

Storage: Store in a well-ventilated place. Keep cool.

Dispose of contents and container in accordance with all local, regional, national and Disposal:

international regulations.

Hazards not

otherwise classified:

Section 3	Compo	Composition/ Information on Ingredients		
Substance/mixture:	Mixture	•		
Ingredient name	%	CAS Number	_	
2,2'-oxybisethanol	15 -40	111-46-6	_	
2,2'-oxybisethanol	7 - 13	111-46-6		

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### First Aid Measures Section 4

### Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-tomouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire. symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Page 3 of 11

**Skin contact**: Get medical attention immediately. Call a poison center or physician. Flush

contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

**Ingestion**: Get medical attention immediately. Call a poison center or physician. Wash out

mouth with water . Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in a recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

# Most important symptoms/effects, acute and delayed Potential acute health effects

**Eye contact**: Causes serious eye damage.

**Inhalation**: No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation.

**Ingestion**: Harmful if swallowed.

### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following: pain, watering, redness.

**Inhalation**: No specific data.

**Skin contact**: Adverse symptoms may include the following: pain or irritation, redness,

blistering may occur

**Ingestion**: Adverse symptoms may include the following: stomach pains.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

# Protection of first aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5

### **Fire-Fighting Measures**

### Extinguishing media

Suitable extinguishing media

**Suitable extinguishing**: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing: None known.

media

Specific hazards arising from the chemical

:

In a fire or if heated, a pressure increase will occur and the container may

burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide, carbon monoxide, nitrogen oxides,

metal oxides/oxides.

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in

positive pressure mode.

### Section 6

## **Accidental Release Measures**

## Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

# For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

# Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Methods and materials for containment and cleaning up

### Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal disposal contractor.

### Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7

# Handling and Storage

### Precautions for safe handling

### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8).

Do not get in eyes or on skin or clothing. Do not breathe vapor or mist.

Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignitions source. Use explosion-proof electrical (ventilating, lightning and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse containers.

# Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage including any incompatibilities

: Storage temperature 5 to 35 deg. C (41 to 95 deg F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8 Exposure Controls/ Personal Protection **Control parameters** Occupational exposure limits Ingredient name Exposure limits OARS WEEL (United States, 7/2018). 2,2' - oxybisethanol TWA: 10 mg/m3 8 hours. 2,2'- oxybisethanol OARS WEEL (United States, 7/2018). TWA: 10 mg/m3 8 hours. ACGIH TLV (United States, 3/2018). 2-aminoethanol STEL: 15 mg/m3 15 minutes STEL: 6 ppm 15 minutes TWA: 7.5 mg/m3 8 hours TWA: 3 ppm 8 hours NIOSH REL (United States, 10/2016). STEL: 15mg/m3 15 minutes STEL: 6 ppm 15 minutes TWA: 8 mg/m3 10 hours TWA: 3 ppm 10 hours OSHA PEL (United States, 5/2018). TWA: 6 mg/m3 8 hours TWA: 3 ppm 8 hours OSHA PEL 1989 (United States, 3/1989). STEL: 15 mg/m3 15 minutes STEL: 6 ppm 15 minutes TWA: 8 mg/m3 8 hours TWA: 3 ppm 8 hours Appropriate engineering

# Appropriate engineering control

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

## **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gasses or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be

required instead.

## **Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. Is should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

# Section 9 Physical and Chemical Properties

**Appearance** 

Physical state : Liquid Color : Black

: Not available Odor Odor threshold : Not available На : Not available : Not available Melt point/Freeze point **Boiling point** : Not available Flash point : Not available : Not available **Evaporation rate** Flammability (solid, gas) : Not available Lower & upper explosive : Not available

(flammable) limits

Vapor pressure: Not availableVapor density: Not availableRelative density: Not availableSolubility: Not availablePartition coefficient:: Not available

n-octanol/water

Auto-ignition temperature: Not availableDecomposition temperature: Not availableViscosity: Not availableDensity: 10.164 lbs/gal

VOC data

VOC % by weight : 47.2 VOC % by volume : 51.87 VOC lbs/gallon : 4.8 VOC lbs/gal less water : 4.8 Section 10 Reactivity and Stability

**Reactivity**: No specific test data related to reactivity available for this product or

its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions

reactions will not occur.

Conditions to avoid : No specific data. Incompatible materials : No specific data.

**Hazardous decomposition**: Under normal conditions of storage and use, hazardous

decomposition products should not be produced.

# Section 11 Toxicological Information

# Information on toxicological effects Acute toxicity

Ingredient name	Result	<b>Species</b>	<u>Dose</u>	<b>Exposure</b>
2,2'-oxybisethanol	LD50 Dermal	Rabbit	11890 mg/kg	-
	LD50 Oral	Rat	12000 mg/kg	-
2,2'-oxybisethanol	LC50 Inhalation dusts & mists	Rat	>4.6 mg/l	4 hours
	LD50 Dermal	Rabbit	11890 mg/kg	-
	LD50 Oral	Rat	12000 mg/kg	-
2-aminoethanol	LD50 Oral	Rat	1720 mg/kg	-

Specific target organ toxicity (single exposure)

<u>Name</u> <u>Category</u> <u>Route of exposure</u> <u>Target organs</u>

2-aminoethanol Category 3 Not applicable Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

NameCategoryRoute of exposureTarget organs2,2'-oxybisethanolCategory 2InhalationNot determined

**Aspiration hazard** 

Not available.

Information on the likely : Not available.

routes of exposure

Potential acute health effects

**Eye contact** : Causes serious eye damage..

**Inhalation**: No known significant effects or critical hazards.

Skin contact: Causes skin irritation.Ingestion: Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain, watering, redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation, redness, blistering may occur

**Ingestion** : Adverse symptoms may include the following:

stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

### Potential chronic health effects

Not available

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity

Numerical measures of toxicity
Acute toxicity estimates

N/A

# Section 12

## **Ecological Information**

### **Toxicity**

Not available.

### Persistence and degradability

Not available.

## **Bioaccumulative potential**

Not available.

Mobility in soil
Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13

### **Disposal Considerations**

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Page 10 of 11

Section 14 Transportation Information

DOT TDG IMDG IATA

**Classification** Classification

**UN Number** Not applicable Not applicable Not applicable

UN proper shipping name

Transport hazard Class(es)

**Packing group** 

Environmental hazards

Additional information

**Special precautions for user**: **Transport within user's premises**: always transport in closed

containers that are upright and secure. Ensure that persons

transporting the product know what to do in the event of an accident or

spillage.

Section 15 Regulatory Information

**U.S. Federal regulations** : All components of this product ar listed as active or exempt from

the TSCA chemical inventory.

SARA 311/312

Classification :

California Prop. 65

WARNING: This product can expose you to Carbon black, which is known to the State of California to

cause cancer. For more information go to www.P65Warnings.ca.gov

International Regulations

**Canadian lists** 

Canadian NPRI : None of the components are listed.
CEPA Toxic Substances : None of the components are listed.

Canada Inventory : Not determined.

## Section 16 Other Information

Every reasonable effort has been made to ensure that the safety information on this sheet is accurate. But because Mosstype has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no expressed or implied warranties of merchantability or fitness for a particular purpose. Mosstype assumes no liability for injury or incidental or consequential damages arising out of the storage handling, or use of this product. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

### Procedure used to derive the classification

Classification	<u>Justification</u>
ACUTE TOXICITY(oral) - Category 4	Calculation method
SKIN CORROSION/IRRITATION- Category 1B	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY(REPEATED EXPOSURE)	Calculation method
(Respiratory tract irritation) - Category 3	
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE)	Calculation method

. Category 2

Page 11 of 11

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labeling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow= Logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution from Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations